

LARES

The LARES LSB-D12 is a high-output subwoofer system designed to provide high fidelity, low frequency audio reproduction from a relatively small enclosure. The LSB-D12 provides exceptionally linear low frequency extension that integrates seamlessly with LARES full range loudspeakers. This is particularly important for systems that utilize a pipe organ, or when a venue lacks sufficient low frequency information. The LSB-D12 is provided with a flat black painted finish and a black coated steel grille.



LARES LSB-D12 SUBWOOFER

SPECIFICATIONS

System Type:
INFRA Sealed chamber
(1.4 cu. ft.)

Frequency Response:
8 Hz to 95 Hz +/-3 dB
(2 pi Steradians, with
8 Hz Integrator)

Sensitivity:
92 dB SPL @ 80 Hz (1W @ 1m)

Impedance:
8 Ohms

Power Handling:
200 W continuous sine wave
200 W instantaneous peak

Input Connectors:
Cinch 142 screw terminal barrier strip

Low Frequency Transducer:
12" INFRA cone
2.5" Voice coil
80 oz. Magnet

Grille:
16 Gauge black vinyl coated
perforated steel

Optional Hardware:
Rigging points

Enclosure:
18 mm 13-ply birch plywood

Finish:
Black paint

Dimensions:
15"h x 18"w x 15"d (39 cm x 46 cm x 39 cm)

Weight:
39 lbs. (18 kg)

Shipping Dimensions:
18" x 21" x 18" (46 cm x 54 cm x 46 cm)

Shipping Weight:
44 lbs. (20 kg)

LARES Associates
30 Dunbarton Road • Belmont, MA 02478
Tel (617) 484-9266
Fax (617) 484-8620
www.lares-lexicon.com